

ADI *Promotions*

GLOBAL DISTRIBUTION

Promotions by ADI Global Distribution
Valid: 2 January – 29 February 2012



ADEMCO



ADKRD042E

ADEMCO DVR

- 4 ch real time CIF recording, adopt Standard H.264 main profile compression
- Intuitive and user-friendly Graphic User Interface (GUI)
- Express and flexible backup via USB, network
- Pentaplex: preview, record, playback, backup and remote access
- Powerful smart phone surveillance supporting WinCE, Symbian, Google phone, Blackberry and Iphone, compatible with 3G/WiFi



ADKMT171

ADEMCO Monitor

- Slim, Lightweight and Portable Design
- Bright & Vivid Colour Reproduction
- 17" TFT-LCD 1280 x 1024 SXGA
- One Level Operation in OSD
- Scan Type: Over / Under / Full Screen / 1:1
- VESA (75 x 75 mm, 100 x 100 mm)
- Universal Power
- Contrast 800:1
- Wide Viewing Angle
- PAL / NTSC Auto Recognition

VIDEO



Alto – buy 1 get 1 free

CQR Internal Sounder

- Low profile sounder with acoustic signalling and tamper
- Internal Sounder
- 6-14vDC
- EN Grade 3
- 115dB(A) sound output
- White

SO/ALTO/WH

INTRUSION

Honeywell



NX2MPS

NetAXS-123: for web-based access control

- 2 Door Standard Metal Enclosure with power supply and battery
- Easy to install and maintain with Built-in Ethernet, USB support, Power over Ethernet
- Affordable and simple to operate
- Superior scalability (users can purchase the exact amount of access control needed and grow easily as their needs change)

Disclaimer: This product is an individual element of the NetAXS Access Control system.

NX2MPS

ACCESS

VIDEO



Series 65

Series 65 Optical Smoke Detectors

- Wide operating voltage (9Vdc to 33Vdc)
- Advanced electronic technology
- Magnetic test as option
- Average quiescent current 40 microA
- Alarm current 52 mA
- Operating Temperature -2' to + 90°C
- Dimension(dxh): 100 x 42 mm

55000-317

FIRE

Honeywell

Performance

Bullet 550TVL IR Camera

- True Day Night Camera
- 3.8-9.5 mm F1.2 IR corrected aspherical Vari-focal Auto Iris lens
- Digital Slow Shutter (DSS) technology
- Digital Noise Reduction (DNR) removes noise artifacts
- The HB73SX installs easily and quickly



VIDEO

HB73SX

Honeywell

Performance

Internal/External 530TVL Dome Camera

- Rugged indoor/outdoor fixed mini-dome
- Integrated housing protects the camera from dust, dirt and water as well as physical harm
- Built-in fixed lens (f=3.8 mm) and a 3-D axis gimbal
- 1/3" CCD that offers 530 TV lines
- 3-D axis gimbal



HD50X

VIDEO

Honeywell

Performance

External 550TVL IR Dome Camera

- True Day Night Camera
- Fixed 4 mm Lens
- 24 integrated LEDs
- 3-D axis gimbal
- High Resolution images



VIDEO

HD70X

Honeywell

Performance

External 530TVL IR Dome Camera

- True Day Night Camera
- The HD73X installs quickly and easily
- 20 integrated LEDs
- 1/3" CCD that offers crisp, clear horizontal resolution
- 3.8-9.5 mm F1.2 IR corrected aspherical Vari-focal Auto Iris lens



HD73X

VIDEO

Honeywell

IS215TCE

Passive Infrared Motion Sensor

- Compact size
- Range: 12 m x 12 m
- Zero clearance bug guard
- Patented look-down mirror
- Power requirements: 8,5~15,4 VDC, 16mA @ 12 VDC
- Dimensions (h x w x d): 86 x 60 x 38 mm



INTRUDER

IS215TCE

Visonic

For a smart and secure lifestyle

PowerMax® Express with free MCS730 siren

Wireless Security in an Ultra Compact Panel

- 28 wireless + 1 hardwired zones
- Compatible with all Visonic peripherals including two-way wireless sirens and keypads
- Highly cost-effective solution for black-box type installation
- Supports three communication paths: GPRS, GSM and SMS, for high-speed, highly reliable reporting
- Intuitive operation, enrollment and programming
- Small size and stylish, clean design
- Free MCS730 two-way, fully wireless outdoor siren
- Complies with EN50131 grade 2



0-101723 / 0-101425

INTRUDER



SC517/WH/MULTI/G3

Grade 3 Magnetic contact with built-in EOL resistors

- 4 Terminals
- Microswitch tamper
- Selectable end of line resistor
- Magnet detection
- 10 mm Operating gap
- Available in white or brown
- EN50131-2-6 Grade 3



INTRUDER

SC517/WH/MULTIG3



DGA

CDVI DGA self contained keypad

- Backlit keypad
- Cast Aluminium body
- IP64
- 2 relay outputs
- Surface mount
- Free voltage
- Torx® mounting screws
- 100 user codes
- 12V to 24 VAC or 12V - 48 VDC



DGA

ACCESS

ADI Global Distribution

Chatsworth House, Hollinsbrook Park, Roach Bank Road, Bury, BL9 8RN

Order information: Call us on 0161 767 2990 or email sales.uk@adiglobal.com Fax: 0161 767 2999

www.adiglobal.com/uk

